

UPS Tower Line 1000VA / 600W MODEL: GP9TL600



OVERVIEW

The GOPower UPS TL 600W is a smart energy experience designed for medium-sized homes and offices.

The 600W UPS delivers continuous backup for computers, communication systems, and multimedia equipment. Part of the Go&Go products line, you enjoy support and service and notifications for your device. The ideal choice for combining strong performance, convenience, and reliability.



Reliable Power
Backup



Smart App
Control



Full Device
Protection

Specifications

Capacity (VA/W)	1000/600
INPUT	Nominal Voltage (Vac) 230 Operating Voltage Range (Vac) 140~300 Operating Frequency Range (Hz) 50/60 (Auto sensing)
OUTPUT	AC Voltage Regulation (Batt. Mode) ±10% Frequency Range (Batt. Mode) (Hz) 50/60 ±1 Transfer Time (ms) Typical 4-8, 13 Max. Waveform (Batt. Mode) Simulated Sinewave
Battery	Battery Voltage (Vdc) : 24 Typical Recharge Time (hours): 4~6 recover to 90% capacity

Management

LED Display: AC Mode, Battery Mode, Overload, Fault
LCD Display: AC Mode, Battery Mode, Load Level,
Battery Level, Input Voltage, Output Voltage, Overload,
Fault, and Battery Low
Alarm: Battery mode, Battery low, overload, Battery
replacement, Fault
Communication Port: USB or RS232(Supports
Windows® 2000/2003/XP/Vista/2008, Windows® 7,
Linux, Unix, and MAC)

Housing

Dimensions	353×149×162(W*D*H)
Weight	7.8 (kg)
Humidity	0~90%RH @ 0~40°C (Non condensing)