

UPS Tower Line

600VA / 360W

MODEL: GP9TL360



OVERVIEW

The GOPower UPS TL 360W is compact and reliable backup solution for home or small office use.

The 360W UPS delivers continuous backup for computers, communication systems, and multimedia equipment. Part of the Go&Go products line, you enjoy support and service and notifications for your device. The ideal choice for combining strong performance, convenience, and reliability.



Reliable Power
Backup



Smart App
Control



Full Device
Protection

Specifications

Capacity (VA/W)	600/360
INPUT	Nominal Voltage (Vac) 230 Operating Voltage Range (Vac) 140~300 Operating Frequency Range (Hz) 50/60 (Auto sensing)
OUTPUT	AC Voltage Regulation (Batt. Mode) ±10% Frequency Range (Batt. Mode) (Hz) 50/60 ±1 Transfer Time (ms) Typical 4-8, 13 Max. Waveform (Batt. Mode) Simulated Sinewave
Battery	Battery Voltage (Vdc) : 12 Typical Recharge Time (hours): 4~6 recover to 90% capacity

Management

LED Display: AC Mode, Battery Mode, Overload, Fault
LCD Display: AC Mode, Battery Mode, Load Level,
Battery Level, Input Voltage, Output Voltage, Overload,
Fault, and Battery Low
Alarm: Battery mode, Battery low, overload, Battery
replacement, Fault
Communication Port: USB or RS232(Supports
Windows® 2000/2003/XP/Vista/2008, Windows® 7,
Linux, Unix, and MAC)

Housing

Dimensions	298×101×142(W*D*H)
Weight	4.3 (kg)
Humidity	0~90%RH @ 0~40°C (Non condensing)